ENVIRONMENTAL PROTECTION



DATASHEET

CEMO Battery charging cabinet 8/5, Premium

Order number: 12110







Product front view open with displayed contents or with optional accessories

Product front view closed





Product front view open

Product open, diagonally from the left

Product open, diagonally from the left with displayed contents or with optional accessories





Product closed, diagonally from the left

TECHNICAL DATA

Medium	Lithium batteries
Dimensions	66 x 52 x 81 cm
Internal dimensions	53 x 45 x 73 cm
Weight	86 kg
Package Weight	102 kg
TÜV Nord Certification	44 780 23136701
Installation Location	indoor



Material	non-combustible building material
Coating	HPL (high pressure laminate)
Container Colour	grey
Door Colour	orange
Operating Voltage	230 V
Maximum power	3500 W (16 A)
Frequency	50/60 Hz
Fan Noise Level	33
Permissible Energy	3021.2 Wh
Load Capacity per Storage Level	30 kg / Level
Stackable	3-high
Forkliftable	no
Permissible Energy Per Storage Level	1510.6 Wh
Assembly condition	mounted
Plug	protective contact

EQUIPMENT

Number of Doors	2
Door Model	double hinged doors
Door Lock Type	T-handle with 2 point locking
Mechanical Ventilation	Yes
Door Contact Switch	Yes
Number of Power Sockets	1x9
Volt-Free Contact	Yes
Storage Levels	2
Number of Shelves	1
Shelf Material	powder-coated steel
Smoke Detector	electric
Temperature Detection	thermal fuse
Display	no
Warning Signal	audible
Alarm Transmission	no
Vermiculite	no

SUITABLE MEDIA

Lithium Battery

LOGISTICS

Package dimensions	80 x 67 x 120 cm
Units per box	0.00
Pallet Dimensions	80 x 67 x 120 cm
Pallet weight	0 kg

APPROVAL







VDMA standard sheet 24994:2024-08

ACCESSORIES











11345 - Fireproof cable entry

11368 - Stacking feet 11389 - Combination 11461 - Castor rack set (8/5) for Licabinets

alarm unit, visual and for battery cabinet audible alarm (100dB)

8/5 240 kg loading capacity

11562 - Rack, for up to two cabinets, including wall mounting(only in combination



Link to product