

DATASHEET

CEMO Battery charging cabinet 8/10 Premium Plus, 230 V, with castors

Order number: 12124



Product front view open



Product <p>front view open with displayed contents or with optional accessories</p>



Product front view closed



Product open, diagonally from the left



Product <p>open, diagonally from the left with displayed contents or with optional accessories</p>



Product closed, diagonally from the left

lock**EX**2.0
inside

TECHNICAL DATA

Medium	Lithium batteries
Dimensions	66 x 115 x 89 cm
Internal dimensions	53 x 88 x 73 cm
Weight	152 kg
Package Weight	174 kg

VDMA Certification	I
TÜV Nord Certification	44 780 23136701
Installation Location	indoor
Material	non-combustible building material
Coating	HPL (high pressure laminate)
Container Colour	grey
Door Colour	orange
Operating Voltage	230 V
Maximum power	3500 W (16 A)
Frequency	50/60 Hz
Fan Noise Level	33
Permissible Energy	6320 Wh
Load Capacity per Storage Level	30 kg / Level
Stackable	no
Forkliftable	Yes
Permissible Energy Per Storage Level	1580 Wh
Assembly condition	mounted
Plug	protective contact

EQUIPMENT

Feet/Castors	castors
Number of Doors	2
Door Model	double hinged doors
Door Lock Type	T-handle with 2 point locking
Mechanical Ventilation	Yes
Door Contact Switch	Yes
Number of Power Sockets	2x9
Volt-Free Contact	Yes
Storage Levels	4
Number of Shelves	3
Shelf Material	powder-coated steel
Smoke Detector	electric
Temperature Detection	temperature sensor
Display	Yes
Warning Signal	audible
Alarm Transmission	Yes

SUITABLE MEDIA

Lithium Battery

LOGISTICS

Package dimensions	80 x 130 x 120 cm
Units per box	0.00
Pallet Dimensions	80 x 130 x 120 cm
Pallet weight	174 kg

APPROVAL



VDMA standard sheet
24994:2024-08



ACCESSORIES



11345 - Fireproof
cable entry



11389 - Combination
alarm unit, visual and
audible alarm
(100dB)



11561 -

[Link to product](#)

