



BRIDGEHILL®
WE SIMPLY BLOCK FIRE

FIRST RESPONDER

CAR STANDARD/ CAR STANDARD XL



Product information

- **NEW** red center stripe for easier deployment
- **NEW** red and yellow handles for improved usability
- **NEW** red center markings on both sides for quick orientation
- Rapidly controls fires in any vehicle
- Effectively isolates fires in electric vehicles
- Immediately contains toxic gases and smoke, protecting civilians from carcinogen exposure
- Suitable for isolating any type of fire
- Delivered in a compact, portable smart bag
- EN 13501-1: Reaction to fire classification A1
- EN ISO 1182
- EN ISO 1716

Car Fire blanket sizes:

- **Car Standard:** $\pm 6 \times 8 \text{ m}$ / $\pm 28 \text{ kg}$
- **Car Standard XL:** $\pm 7.5 \times 10 \text{ m}$ / $\pm 42 \text{ kg}$

Ideal for locations with a high density of parked vehicles

Parking garages – Charging stations – Ferries – Gas stations – Workshops – Car dealers – Tunnels – Parking lots



How to use

Handled by:

1. Place the fire blanket on the ground. Center it in front of or behind the car, then roll it out. The fire blanket is usable on both sides.
2. Two people should each grab a handle and carefully pull the fire blanket over the car in one continuous motion.
3. Ensure the fire blanket is snug against the ground, covering 50 cm on each side to cut off the oxygen supply. Wait for firefighters to evaluate the situation further.



For instructional videos, scan the QR code.



Fires in Electric Vehicles:

In many cases, a loud buzzing sound may indicate thermal runaway. We recommend keeping the fire blanket on the vehicle until it has been transported to a safe location and inspected by the fire department. Please note that a battery fire can reignite at any time.



BRIDGEHILL®
WE SIMPLY BLOCK FIRE

TECHNICAL SHEET

CAR STANDARD/ CAR STANDARD XL

FIRST RESPONDER

SKU:	• Car Standard: 101252 • Car Standard XL: 101254
Size/Weight:	• Car Standard: $\pm 6 \times 8$ m (48 m²) ± 28 kg (without bag) • Car Standard XL: $\pm 7.5 \times 10$ m (75 m²) ± 42 kg (without bag)
Core material:	380 gsm pyroxene
Coating:	± 50 gsm BridgeTech™ Coating In fires with high levels of conduction heat, flames may appear from the coating of the fire blanket. This will not alter the performance of the fire blanket.
Car sizes:	• Car Standard: Fits vehicles up to standard SUVs like Land Rover and Volvo XC90 • Car Standard XL: Handle larger vehicles like Rivian, Ford F150, etc.
Main usage:	• Fossil fuel vehicles • Electric/hybrid vehicles
Smartbag:	Airtight bag. Smartbag maintenance: Use silicon grease on the zipper to keep the bag airtight.
Shelf life:	Ten (10) years.

Technical specification:

Core Fabric			Unit	Tolerance
Yarn	Warp Weft	300 165	Tex Tex	$\pm 5\%$
Yarn count	Warp Weft	8.0 8.0	Ends/cm Ends/cm	$\pm 5\%$
Tensile strength (typical)	Warp Weft	3200 2500	N/50mm N/50mm	$\geq$
Thickness	–	0.40	Mm	$\pm 5\%$
Weave pattern	–	Plain	–	–
Service temperature on core fabric	Short term ± 1600 °C Long term ± 800 °C			

WARNING:

Avoid inhaling smoke from the burning vehicle.

Do not put yourself at unnecessary risk, call the fire department!