ENVIRONMENTAL PROTECTION



DATASHEET

CEMO Battery charging cabinet Basic 8/20 230 V, with feet

Order number: 12048



Product closed with displayed contents or with optional accessories





Product detail view

Product detail view



TECHNICAL DATA

Medium	Lithium batteries
Dimensions	66 x 213 x 80 cm
Internal dimensions	53 x 176 x 73 cm
Weight	267 kg
Package Weight	287 kg
Installation Location	indoor
Material	non-combustible building material
Coating	HPL (high pressure laminate)
Container Colour	grey
Door Colour	orange
Operating Voltage	230 V
Maximum power	3500 W (16 A)
Frequency	50/60 Hz
Fan Noise Level	33
Permissible Energy	12640 Wh
Load Capacity per Storage Level	30 kg / Level
Stackable	no
Forkliftable	Yes
Permissible Energy Per Storage Level	1580 Wh
Assembly condition	mounted
Plug	protective contact



EQUIPMENT

Feet/Castors	feet
Number of Doors	4
Door Model	double hinged doors
Door Lock Type	T-handle with 2 point locking
Mechanical Ventilation	Yes
Door Contact Switch	Yes
Number of Power Sockets	4x9
Volt-Free Contact	no
Storage Levels	8
Number of Shelves	6
Shelf Material	powder-coated steel
Smoke Detector	battery-powered
Temperature Detection	thermal fuse
Display	no
Warning Signal	audible
Alarm Transmission	no
Vermiculite	no

SUITABLE MEDIA

Lithium Battery

LOGISTICS

Package dimensions	80 x 228 x 120 cm
Units per box	1.00
Units per pallet	1
Pallet Dimensions	80 x 228 x 120 cm
Pallet weight	287 kg

APPROVAL



VDMA standard sheet 24994:2024-08

ACCESSORIES

Datasheet CEMO Battery charging cabinet Basic 8/20 230 V, with feet







11345 - Fireproof cable entry

11508 - Insert shelf (for floor level or as intermediate level)

11561 -

11658 - Second smoke detector (can be networked with internal smoke detector)

